



2210

Netopia® ADSL2+ Gateway

The Motorola Netopia 2210 ADSL2+ Gateway delivers exceptionally high value for residential customers connecting to ADSL2+ networks for high-speed Internet access.

Highlights

Affordable Value

Highly integrated design to meet sensitive cost targets for large-scale deployments

Customer-Friendly

Available CD-less installation and robust management feature boost customer satisfaction and reduce support costs

Remote Management

Configured to enable automated service provisioning, embedded software updates, and service activation without subscriber intervention or unnecessary truck-rolls

"Zero-Touch" Subscriber Experience...

The 2210 ADSL2+ is a single-port gateway, perfect for the single-PC residential user who needs simple connectivity. Featuring Motorola's legendary ease of use, reliability, and security, the 2210 also offers automated provisioning capabilities. On the first connection to the network, the 2210 gateway can be configured to automatically "phone home" to the service provider, enabling automated service provisioning, embedded software updates, and service activation—all without subscriber intervention.

...And An Intuitive Wizard When Needed

For installations that are not configured for automated provisioning, the intuitive installation wizard guides even novice users through easy-to-follow set-up instructions.

Integrated Firewall, Intelligent Diagnostics, and Remote Management Mean Fewer Support Calls

The robust security features include a built-in stateful firewall to protect single-user households from hackers and denial-of-service (DoS) attacks.

Intelligent software features and diagnostics reduce the cost of ongoing customer support while increasing customer satisfaction. The integrated Point-to-Point Protocol over Ethernet (PPPoE) client eliminates extra software licensing costs and dramatically reduces support calls.

Support for the DSL Forum TR-069 remote management specification ensures comprehensive remote manageability, including centralized remote provisioning, troubleshooting, and management.

DATA SHEET

2210
Netopia ADSL2+ Gateway

INTERFACES

WAN Interface	ADSL2+ (RJ-11)
LAN Interface	Single-port 10/100 Ethernet (RJ-45) with Auto-MDIX crossover
LEDs	Power, Ethernet, DSL, Internet Status

ADSL SUPPORT

ANSI T1.413 Issue 2
ITU 992.1 (ADSL), 992.3 (ADSL2), 992.5 (ADSL2+),
ITU G.992.3 and G.992.5 Annex L (RE-ADSL2/2+), ITU G.992.3
Amendment 1 and 2 and G.992.5 Amendment 2, Annex A and
Annex B, Annex M
DSL Forum TR-067 and TR-100

NETWORK PROTOCOL SUPPORT

RFC 2516 PPP over Ethernet (PPPoE)
RFC 2364 PPP over ATM (PPPoA)
RFC 1483/2684 Bridged Ethernet
RFC 1483/2684 Routed IP
DSL Forum TR-101
IEEE 802.1Q VLAN
IPoE
DHCP client, server, and relay, DHCP option support and filter
rules
Dynamic DNS
ATM Adaptation Layer 5 Eight Permanent Virtual Circuits, UBR,
CBR, VBRnrt, VBRrt, ITU-T I.610
(F4, F5) OAM
PPP PAP, CHAP, IPCP, LCP

PACKET FORWARDING

IPv4, static routes, RIP1 and RIP2
TCP, UDP, ARP, ICMP
NAPT NAT pass-through pinhole,
application-level gateway
Diffserv EF, AF, BE, NC, weighted fair
queuing
IGMP v1, v2, v3 IGMP proxy, fast join/leave, IGMP
snooping

SECURITY

Stateful firewall
Denial-of-Service protection
VPN pass-through for PPTP, L2TP, IPSec

DEVICE MANAGEMENT

Remote Management TR-069, TR-104, Web UI, CLI (Telnet)
Local Management TR-064, UPnP, Web UI, CLI (Telnet)
Utilities Ping, traceroute, reverse DNS
Two-level password-protected access
Statistic and log reporting, remote syslog
Seven-layer diagnostics

LANGUAGE SUPPORT

English, French, German, Italian, Portuguese (Brazil), Spanish
(Latin America)

REGULATORY

US FCC Part 68, Part 15, Class B,
UL 60950; CEC-compliant power
supply
Canada CS-03, ICES-003, CUL, CSA
Europe R&TTE, EN300 386, K.21;
RoHS-compliant

ENVIRONMENTAL

Operating Temperature 32 °F to 104 °F (0 °C to 40 °C)
Storage Temperature -40 °F to 185 °F (-40 °C to 85 °C)
Relative Humidity 5 to 90% (non-condensing)

WEIGHT AND DIMENSIONS

Weight 0.9 lb (408 g)
Dimensions 4.4 in L x 3.4 in W x 1.2 in H
(112 mm x 86 mm x 30 mm)
Horizontal or vertical desktop placement; wall-mounting
keyholes

COMPATIBILITY

PC Windows® 98, 98SE, ME, 2000,
XP SP2, Vista
Macintosh® Mac OS X

All features, functionality, and other product specifications are subject to change
without notice or obligation.