

4410A Specifications

ELECTRICAL SPECIFICATIONS


- GPS Antenna input: BNC female with 5 V on center conductor
- 10 MHz Sine output (4)
 - Connector: BNC female
 - Level: 13 ± 1 dBm
 - Impedance: $50 \pm 5\Omega$
 - SSB Phase noise
 - 10 Hz -90 dBc/Hz
 - 100 Hz -128 dBc/Hz
 - 1 kHz -140 dBc/Hz
 - 10 kHz -148 dBc/Hz
 - 100 kHz -148 dBc/Hz
 - Long term stability in Holdover: $<5 \times 10^{-11}$ per month
- 10 MHz TTL Output (1)
 - Connector: BNC female
 - Level: 3 V into 50Ω
- 1PPS Output (4)
 - Connector: BNC female
 - Level: 4.5 V into 50Ω
 - Impedance: $50 \pm 5\Omega$
 - UTC Offset accuracy: 50 ns RMS
 - Holdover accuracy: $1 \mu\text{s}$ @ 24 hours
- IRIG-B Modulated output (4)
 - Connector: BNC female
 - Timecode: IRIG-B 123
 - Level: 3 Vpp into 50Ω
 - Impedance: $50 \pm 5\Omega$
 - Accuracy: $7 \pm 2 \mu\text{s}$ relative to 1PPS
- IRIG-B DC Level shift output (2)
 - Connector: BNC female
 - Timecode: IRIG-B 003
 - Level: 4.4 V into 50Ω

ENVIRONMENTAL & PHYSICAL SPECIFICATIONS

- Temperature range: 0°C - 50°C (operating)
- Humidity: 0-95% Non-condensing (operating)
- AC Input: 90 – 264 V AC, 85 W, 47 – 63 Hz
- Dimensions: 1.75" (4.45 cm) H x 19" (48.26 cm) W x 12" (30.48 cm) D
- Weight: 9 lb (4 kg)

OPTIONS

- 001 GPS Antenna
- 002 30 m GPS Antenna cable
- 003 60 m GPS Antenna cable
- 004 Lightning arrestor



Typical Frequency Stability

Rear View