

	8110ME 2-Way		8002ME 3-Way Bal		8112ME 3-Way Unbal		8113ME 4-Way	
INSERTION LOSS	Typical	QA	Typical	QA	Typical	QA	Typical	QA
5-15 MHz	3.3	3.5	5.7	5.6	3.4/6.8	3.7/7.0	6.8	7.0
16-42 MHz	3.4	3.7	5.7	5.7	3.4/6.8	3.7/7.0	6.8	7.0
52-400 MHz	3.6	3.8	5.8	5.9	3.5/7.0	3.8/7.2	6.9	7.1
401-860 MHz	3.7	3.8	5.8	6.0	3.5/7.2	3.8/7.2	7.0	7.2
861-1002 MHz	3.8	3.9	5.9	6.5	3.7/7.3	3.9/7.4	7.2	7.5
1003-1200 MHz	4.0	4.2	6.4	6.7	4.0/7.8	4.1/8.0	7.5	8.0
RETURN LOSS - INPUT PORT								
5-15 MHz	25	22	22	20	22	20	22	20
16-42 MHz	26	25	24	22	24	22	24	22
52-400 MHz	25	22	22	20	22	20	22	20
401-860 MHz	25	22	22	20	22	20	22	20
861-1002 MHz	25	22	22	22	22	22	22	20
1003-1200 MHz	20	18	18	20	18	20	18	16
RETURN LOSS - OUTPUT PORTS								
5-15 MHz	25	23	25	22	25	22	25	22
16-42 MHz	38	35	39	35	39	35	39	35
52-400 MHz	28	25	30	28	30	28	30	28
401-860 MHz	25	22	28	25	28	25	28	25
861-1002 MHz	25	22	26	22	26	22	26	22
1003-1200 MHz	22	20	22	18	22	18	22	18
ISOLATION OUTPUT PORT TO PORT								
5-15 MHz	25	30	25	22	25	22	25	22
16-42 MHz	38	35	38	35	38	35	38	35
52-400 MHz	28	30	28	26	26	26	28	26
401-860 MHz	26	28	26	24	26	24	26	24
861-1002 MHz	24	26	24	22	24	22	24	22
1003-1200 MHz	22	24	18	20	18	20	18	20
PHYSICALS								
Weight (gram)	1.5 oz (42g)		2.1oz (59g)		2.1oz (59g)		2.2 oz (62g)	
Packaging - master ctn	200		200		200		200	

