



RGB MMC Specifications

RGB MMC Rear View

<p>INPUT/OUTPUT INTERFACES</p> <p>ASI</p> <p>Gigabit Ethernet</p> <p>Fast Ethernet</p>	<p>Up to 24 ASI ports per chassis Up to 4 ASI modules with 6 ASI ports each Software configurable as input or output 213 Mbps data rate/port</p> <p>8 SFP interfaces – copper or optical</p> <p>1 10/100BaseT control and management interface</p>
<p>ASI-TO-GIGABIT ETHERNET CONVERSION</p>	<p>DVB-ASI to Gigabit Ethernet conversion Pass-through of all tables including MPEG, DVB and PSIP tables</p>
<p>VIDEO FORMATS</p> <p>MPEG</p> <p>SD and HD Resolutions</p>	<p>All MPEG-2 transport streams carrying MPEG-2, MPEG-4/H.264 and VC-1 compressed programs MPTS, SPTS, multicast and unicast support CBR and VBR support</p> <p>All NTSC and PAL resolutions (transparent)</p>
<p>AUDIO FORMATS</p>	<p>All audio formats (transparent)</p>
<p>REGULATORY COMPLIANCE</p> <p>Safety</p> <p>Electro Magnetic</p>	<p>CE UL, TUV/GS, cTUVus FCC Part 15, Class A, EN55022, EN55024</p>
<p>ELECTRICAL/MECHANICAL</p> <p>Input Power</p> <p>Line Frequency</p> <p>Power Consumption</p> <p>Dimensions</p> <p>Weight</p> <p>Cooling</p>	<p>AC: 100-127 VAC @ 1.4A to 200-240 VAC @ 0.8A DC: 48VDC @ 3.5A (range 36-75VDC)</p> <p>50-60 Hz</p> <p>170 W – fully loaded</p> <p>1 rack unit – 1.75" H x 19" W x 23" L (43.6 H x 433 W x 583 L mm)</p> <p>< 30 lbs. (11.34 kg)</p> <p>Front to back</p>
<p>ENVIRONMENTAL</p> <p>Storage Temperature</p> <p>Operating Temperature</p> <p>Humidity</p>	<p>-40° to 70°C</p> <p>0° to 40°C</p> <p>5% to 95% (non-condensing)</p>