



The PTM-305's vector display.

- Color TFT touch screen LCD
 - 320 x 240 Pixels
 - 54 x 72 mm Display
- Test Signal Generator
 - Test Signals
 - Color Bars:
 - Split Field 75% & 100%
 - Full Field 75% & 100%
 - Multi Burst, Multi Pulse
 - Sweep
 - Sin X
 - Window test signal
 - Freq. Stab. 50ppm
 - EDH insertion
 - Embed Tone in any Single Audio Group
 - Audio Frequency and Amplitude Adjustable
 - Serial Digital Video Output
525/59.94, 625/50
 - Composite Video Output
NTSC-(M/J) or PAL or PAL-M
- Color Picture Monitor
 - Zoom and Pulse Cross Mode
 - Horizontal and Vertical Offset
- Waveform Monitor
 - Composite Video Input
 - Composite or RGB Levels
 - Serial Digital Video Input
 - RGB or Y, Pb, Pr Levels
 - Color Display
 - Digital Line Select
 - Persistence Adjustable
 - Zoom and Pan Mode
- Vectorscope
 - 75% and 100% Display Mode
 - Digital Line Select
 - Persistence Adjustable
- Serial Digital Data Analyzer
 - SAV Position
 - SAV XYZ Word
 - EAV Position
 - EAV XYZ Word
 - ANC Check Sum
 - Active Field CRC
 - Full Field CRC
 - EDH Flags
 - Active Picture EDH
 - Full Field EDH
- Embedded Serial Audio Monitor
 - AES/EBU 48kHz Audio Data Supported
 - Analyze any one pair from 4 groups
 - Stereo Bar Graph Peak Hold Audio Meters
 - Stereo Bar Graph Average Audio Meters
 - 16 Bit Stereo DAC
 - Variable Stereo Headphone output (from embedded audio sources)
- Audio Tone Generator
 - Audio frequency fixed selections
400 Hz, 1 kHz, 10 kHz
 - Audio frequency range selections 10 Hz to 20 kHz in 10 Hz steps
 - Audio amplitude selections: +4, 0, -4, -8, -18, -20 dB, variable
 - Audio amplitude variable range:
+4 dB to -59 dB in 1 dB steps
- Analog Audio monaural tone output:
 - THD: $\leq 1\%$
 - Maximum Level: +4 dBu
 - Connector: Miniature stereo headphone jack
 - 16 bit DAC
- Power Management
 - Auto shutdown of unused functions
 - Up to 4 Hour Operation (Battery) (Function Dependent)
- Serial Digital Output
 - Return Loss > 15db at 270MHz
 - Output Data Rate 270Mb/s
 - Output Jitter ≤ 0.2 UI
- Composite Analog Output
 - 10 bit DAC
 - Interpolation 8:8:8
 - S/N ratio (Ramp) > 60db rms
- Serial Digital Input (SMPTE - 259 M-C)
- Composite Analog Input (NTSC - PAL)
- Physical Specifications
 - 136mm High x 80mm Wide x 35mm Deep
 - 411 grams (14.5 oz)
 - Operating Temperature 0 to 40° C
 - Non Operating Temperature -30 to +85° C
 - Power: 6 "AA" NiMH batteries with battery charger and AC power adapters included.

Harris is a registered trademark of Harris Corporation. Trademarks and tradenames are the property of their respective companies.