



Motorola Cares for the Environment

Motorola believes in "going green" — we have a global commitment to sustaining the environment. Motorola has been working for years to continually improve our environmental profile. We are in step with our customers and their increasing interest in partnering with a company that will help them reduce their carbon footprint, while offering compelling products that will help them grow their eco-conscious customer base.

Motorola Designed the SBG901 Series to Minimize its Impact on the Environment

Motorola's modems comply with international environmental and energy efficient standards, including ENERGY STAR qualified power supplies, European Code of Conduct compliance for both the power supply and modem, and lead-free circuit boards as certified by RoHS compliance.

Packaging

The SBG901 Series uses Motorola's new, environmentally friendly package design: our modems ship in single pack boxes. By both eliminating the suspension plastic and reducing the box size, Motorola is helping to reduce the environmental impact of the SBG901 Series. As an even more impactful step, operators may choose to receive the products in a bulk package, thus reducing the extra waste and transport weight associated with single packages. Motorola's bulk packaging solutions eliminate excess installation CDs and USB cables. Additionally, customers have the option to reduce the number of cables shipped with each unit. The packaging is 100% recyclable. Our packaging is now labeled with standard recycling codes (such as ♻️) to make it easier for our customers to identify recycling opportunities.

Wi-Fi

Wireless Access Point



User-friendly Installation

Motorola's integrated SBG901 includes stateful firewall protection and WEP (Wired Equivalency Privacy). The SBG901 is also equipped with a built-in, easy-to-use Motorola Wi-Fi installation wizard — a 'zero-touch' auto Wi-Fi provisioning tool — which seamlessly configures a secure Wi-Fi connection on a user's machine. When the Wi-Fi wizard is finished, a secure WPA (Wi-Fi Protected Access) encrypted wireless connection is established to the gateway, protecting the user's machine from hacker attacks. Motorola's embedded software enables Wi-Fi deployments with high levels of quality, reliability, and customer satisfaction, with low operational and support costs for the MSO.

Service Assurance

Supporting the Wi-Fi home network is a new challenge for the cable industry. As the leading worldwide provider of DOCSIS® products, Motorola is helping ease cable operators into Wi-Fi delivery. By combining the highest-performing and lowest cost of ownership modems in the industry, with easy-to-use Wi-Fi installation and pairing tools as well as advanced remote management features, the SBG901 is offering an all-in-one approach to broadband home networking. In addition, Motorola's field-proven NBBS device management software provides the MSO with intelligent management, auto-provisioning, and remote management features to improve accuracy, efficiency, and customer satisfaction. These value-adding features enable remote device administration for improved accuracy and reduced support costs. The SBG901 is compatible with Motorola's NBBS scalable, carrier-grade software platform that enables cable operators to remotely access, configure, monitor, and troubleshoot their full portfolio of consumer devices, home networks, and services.

DATA SHEET

SBG901 SURFboard Wireless Cable Modem Gateway

General

The SBG901 Wireless Cable Modem Gateway delivers:

- The speed of a DOCSIS 2.0 cable modem
- The mobility of a wireless LAN and the simplicity of “no new wires” technology
- The security of a firewall

Three networking products in one

Integrated DOCSIS® 2.0 SURFboard cable modem, router with one 10/100 Fast Ethernet port and auto-MDIX cross-over cable detection, and IEEE 802.11b/g wireless access point

Easy setup

An included CD-ROM provides an Installation Assistant, a Wireless Security Set Up Wizard, and multi-lingual product documents

Web-based management

Manage data and wireless network using a Web-based interface

Advanced security

Built-in firewall with stateful Packet Inspection (SPI), intrusion detection, and Denial of Service (DoS) attack prevention

Extensible networking

Network up to 253 desktop computers, laptops, and other Ethernet or wireless devices² to create a full Class C network

Enterprise-capable

VPN pass-through (IPSec, PPTP, L2TP)

STANDARDS COMPLIANCE

IEEE	802.11b/g, 802.11b DSSS, 802.11b/g OFDM, 802.1d, 802.3, 802.3u, 802.31CPE
Data	DOCSIS 2.0
Wireless	Wi-Fi Alliance Certified

WLAN RF CENTER FREQUENCY RANGE

North America	2.412 GHz to 2.462 GHz
---------------	------------------------

DATA RATE AND MODULATION TYPES

1 Mbit/s DBPSK; 2 Mbit/s DQPSK; 5.5 Mbit/s, 11 Mbit/s CCK; 6 Mbit/s, 9 Mbit/s, 12 Mbit/s, 18 Mbit/s, 24 Mbit/s, 36 Mbit/s, 48 Mbit/s, 54 Mbit/s OFDM Options

INTERFACES

Cable interface	F-connector, female, 75 Ω
CPE wired interface	10/100 Fast Ethernet (auto-sensing)
CPE wireless interface	802.11b/g
Data protocol	TCP/IP

NETWORK MANAGEMENT

SNMP v1, v2c, v3; IP v4 addressing; LAN-side DHCP server; NAT, NAPT

TRANSMIT POWER

17 dBm (EIRP) in 802.11 g Mode; 20 dBm (EIRP) in 802.11b Mode

RECEIVE SENSITIVITY*

-74 dBm at 54 Mbps

Downstream

MODULATION

64 or 256 QAM

MAXIMUM DATA RATE³

DOCSIS ≤ 38 Mbps

BANDWIDTH

DOCSIS 6 MHz

SYMBOL RATES

64 QAM 5.069 Msym/s, 256 QAM 5.361 Msym/s

OPERATING LEVEL RANGE

-15 to 15 dBmV

INPUT IMPEDANCE

75 Ω (nominal)

FREQUENCY RANGE

88 to 860 MHz

Upstream

MODULATION

8***, 16, 32***, 64***, 128**** QAM or QPSK

MAXIMUM DATA RATE³

30 Mbps

BANDWIDTH

200 kHz, 400 kHz, 800 kHz, 1.6 MHz, 3.2 MHz, 6.44 MHz

SYMBOL RATES

160, 320, 640, 1280, and 2560, and 51204 ksym/s

OPERATING LEVEL RANGE⁴

A-TDMA	8 to 54 dBmV (32 and 64 QAM) 8 to 55 dBmV (8 and 16 QAM) 8 to 58 dBmV (QPSK)
S-CDMA	8 to 53 dBmV (all modulations)

OUTPUT IMPEDANCE

75 Ω (nominal)

FREQUENCY RANGE

DOCSIS 5 to 42 MHz (edge to edge)

Network

GATEWAY

DHCP, NAT, VPN tunneling; static routing and dynamic IP routing; SPI firewall with DoS protection and intrusion prevention; port, packet, and URL keyword filtering; full suite of ALGs; UPnP IGD 1.0

WIRELESS LAN

802.11b/g Wi-Fi

NETWORK MANAGEMENT

SNMP v1, v2c, v3, IP v6 addressing; LAN-side DHCP server; NAT, NAPT

Wireless device and its corresponding networks supportable by Motorola's NBBS Management System

802.11i SECURITY

WEP-64/128, WPA-PSK, WPA, WPA2, TKIP, AES, 802.1x, 802.11i (pre-authentication)

DEVICE PAIRING

User-friendly Wi-Fi protected setup (WPS) for secure WPS compatible device pairing

*** With A-TDMA or S-CDMA enabled CMTS

**** With S-CDMA enabled CMTS

* Receiver sensitivity indicated under ideal conditions.

DATA SHEET

SBG901 SURFboard Wireless Cable Modem Gateway

Network, cont.

¹ Certain features may not be activated by your service provider, and/or their network settings may limit the feature's functionality. Additionally, certain features may require a subscription. Contact your service provider for details. All features, functionality, and other product specifications are subject to change without notice or obligation. Motorola shall not be liable for, and expressly disclaims, any direct or indirect liabilities, damages, losses, claims, demands, actions, causes of action, risks, or harms arising from or related to the services provided through this equipment. Important: Be aware that you will not be able to make any calls using this VoIP device if your broadband connection is not functioning properly.

² Actual speeds will vary, and are often less than the maximum possible. Upload and download speeds are affected by several factors, including, but not limited to, network traffic and services offered by your cable operator or broadband service provider, computer equipment, type of server, number of connections to server, and availability of Internet router(s).

³ Actual speeds will vary. Maximum speeds are only attainable with A-TDMA or S-CDMA technology.

⁴ Older versions of Windows, although not specifically supported, will work with this cable modem.

REGULATORY DOMAINS

To include US, Canada, ETSI, World

TRANSMIT POWER OUTPUT

IEEE 802.11b	20 dBm (EIRP)
IEEE 802.11g	17 dBm (EIRP)

RECEIVER SENSITIVITY

-74 dBm at 54 Mbps

Electrical

INPUT VOLTAGE RANGE

100 to 240 VAC, 50 to 60 Hz

POWER CONSUMPTION

9 W (nominal)

Physical

TEMPERATURE

Operating	32 °F to 104 °F (0 °C to 40 °C), -150 to 10,000 ft
Storage	-22 °F to 158 °F (-30 °C to 70 °C)

HUMIDITY

5% to 95% (non-condensing)

DIMENSIONS

5.7 in H x 5.7 in W x 1.5 in D
(146.0 mm x 146.0 mm x 38.0 mm)

WEIGHT

15 oz (0.42 kg) (unit only)

Compatibility

PLATFORM

PC	90496, Pentium, or later; Windows® Vista™, 2000, or XP; or Linux with Ethernet connection ⁴
Macintosh®	Power PC or later; OS 9 or higher; Ethernet connection
UNIX®	Ethernet connection
Home Networking	Ethernet router or wireless access point

Environmental

Power supply meets H.R.6, EnergyStar, and CoC (European Code of Conduct) requirements
100% recyclable packaging
Unit meets CoC requirements for Energy Consumption of Broadband Equipment
Unit is RoHS compliant (lead free)